


World-class Tile and Stone
Installation **Solution**



M.F.G By.
GANGA PRODUCTS
Panchasar Road, Morbi 363641 (Guj.) INDIA.
Cell :- +91 98257 98390
E-mail :- duratoneproducts@gmail.com • Web : www.duratoneproducts.in



World-class Tile and Stone
Installation **Solution**

ABOUT US

Duratone Chemical company is considered as one of the leading supplier of Construction chemical product in India. Duratone Construction Chemical company is an ISO 9001-2015 Certified Company. Duratone is Fastest growing Indian company in the field of construction chemical with the brand name of Duratone. Our product range of construction chemical such as epoxy and grout, adhesives, admixtures, sealers and other for various application like grouting, fixing of tiles, waterproofing etc.

COMPANY STRATEGY

- Our world is nothing more than the extension of our personality - A signature that is individual and unique, an irreplaceable stamp of our soul.
- Our choice leads us and our taste defines us.
- Core values - we believe in treating our customers with respect and faith. We integrate honesty, integrity and business ethics into all aspects of our business functioning.
- **Mission** - To build long term relationships with our customers and provide exceptional customer services by pursuing business through innovation and advanced technology.
- Purpose to be a leader in constructions chemical industry by providing enhanced Product, services, relationship and profitability.



World-class Tile and Stone
Installation **Solution**

INDEX

ADHESIVES

Duratone Copper Grey.....	02
Duratone Silver Grey.....	04
Gold / Grey / White.....	06
Platinum White / Grey.....	08

GROUTS

Duratone Tile Grout.....	10
Duratone Epoxy Grout.....	12
Duratone Sparkle Epoxy Grout.....	14
Duratone Admix.....	16
Duratone Tiles Cleaner.....	18

WATER PROOFING

Duratone Cam Bond.....	20
Duratone Super Latex.....	22
Duratone Wall Putty.....	24
Duratone CLW+.....	26

World-class Tile and Stone
Installation **Solution**



DURATONE COPPER GREY

DURATONE COPPER GREY

Interior / Exterior Floor Tile Adhesive



APPLICATION

Polymer modified grey cement based tile adhesive for fixing ceramic tiles, natural stone & vitrified tiles in interior area

KEY FEATURES & BENEFIT

- Single component just add water
- Polymer modified
- High bond strength
- Economical & easy to use

COVERAGE

Coverage is based on smoothness of substrate and thickness of mortar used. For a 3mm bed thickness the coverage will be 55-60 Sq.Feet per 20 kg. Bag.

SELF LIFE & STORAGE

Best Before 12 Month from the date of manufacturing in unopened condition. Store in a cool & dry place

Packing
20 kg

World-class Tile and Stone
Installation **Solution**



DURATONE SILVER GREY

DURATONE SILVER GREY

Interior Wall & Floor Tile Adhesive (Tile on Tile)



APPLICATION

Ideal for fixing ceramic tiles indoor and outdoor areas. Vitrified tiles only indoor areas also use in tile on tile application. Applying in window & door framing

KEY FEATURES & BENEFIT

- Single component just add water
- Polymer modified
- High bond strength
- Better Work ability
- Cost Efficient

COVERAGE

Coverage is based on smoothness of substrate and thickness of mortar used. For a 3mm bed thickness the coverage will be 55-60 Sq.Feet per 20 kg. Bag.

SELF LIFE & STORAGE

Best Before 12 Month from the date of manufacturing in unopened condition. Store in a cool & dry place

Packing
20 kg

**World-class Tile and Stone
Installation Solution**



GOLD / GREY / WHITE

GOLD / GREY / WHITE

Interior / Exterior wall & Floor Tile
Nature Stone Adhesive



APPLICATION

Very high polymer modified cement based adhesive for fixing big size tiles and natural stone in interior & exterior wall & floor application

KEY FEATURES & BENEFIT

- Single component just add water
- Easy to use & better work ability
- Water Resistant
- Excellent Adhesion & strength
- Ensure permanent fixing

COVERAGE

Coverage is based on smoothness of substrate and thickness of mortar used. For a 3mm bed thickness the coverage will be 55-60 Sq.Feet per 20 kg. Bag.

SELF LIFE & STORAGE

Best Before 12 Month from the date of manufacturing in unopened condition. Store in a cool & dry place

Packing
20 kg

World-class Tile and Stone
Installation **Solution**



PLATINUM WHITE / GREY

PLATINUM WHITE / GREY

Fixing of white marble slabs, glass mosaic, internal & external wall, floor surface & swimming pool



APPLICATION

Very highly polymer modified cement based flexible adhesive for large format vitrified tiles and natural stone in inferior & exterior wall & floor application

KEY FEATURES & BENEFIT

- Single component just add water
- Highly polymer modified
- Easy to use & better work ability
- Water and sock resistant
- Bonds to various substrates
- Excellent Adhesion & flexural strength
- Ensure permanent installation

COVERAGE

Coverage is based on smoothness of substrate and thickness of mortar used. For a 3mm bed thickness the coverage will be 55-60 Sq.Feet per 20 kg. Bag.

SELF LIFE & STORAGE

Best Before 12 Month from the date of manufacturing in unopened condition. Store in a cool & dry place

Packing
20 kg

World-class Tile and Stone
Installation **Solution**



DURATONE TILE GROUT

DURATONE TILE GROUT

Interior / Exterior wall & Floor Tile Joint Grout



DESCRIPTION High quality fine, polymer-modified, water-resistant, cement-based powder grout designed for grouting glazed wall tiles, mosaics, vitrified & fully vitrified tiles, floor tiles, industrial floor tiles etc.,

FEATURES Polymer modified grout.
Good compressive strength.
Available in range of colours

COVERAGE Depends on substrate

Packing
500gm, 1kg

Available colours

White	Ivory	Grey	Dark Grey
Light Blue	Pink	Light Green	Dark Brown
Magenta	Wooden	Orange	Jesalmer
Sandle Paste	Yellow	Red Brown	Terracotta
Bottle Green	Alpen Blue	C. Brown	Black

World-class Tile and Stone
Installation Solution



EPOXY GROUT

EPOXY GROUT

Stain Free Grout for Floor & Wall (3 Part)



DESCRIPTION Epoxy Grout is a three-part system, comprising of PART A, PART B and PART C for ease of application. The ability to fill tile / stone joints. The grout is best mixed to a smooth, creamy consistent paste. Epoxy resin-based grout has a high degree of resistance to chemicals, abrasion and higher impact resistance. The cured grout creates a tough, impermeable layer resistant to food drops, bacteria, and dirt is easily maintained in a sanitary condition.

FEATURES Stain less and easy to clean, easy to mix and apply.
Provides excellent chemical resistant property.
Provides hygienic, hard wearing & impervious properties.
Non-cracking or powdering.
Non-Toxic & restricts entry of bacteria / dirt.

Technical Specification

JOINT WIDTH	POT LIFE @ 27 +/- 2C°	CURE @ 27 +/- 2C°	TEMPERATURE RESISTANCE	WATER ABSORPTION	SPECIFIC GRAVITY
2-20mm	45 minutes	48hours	Prolonged - 30°C To 150° c intermittent up to 100 c°	Nil (1)	1.75
TENSILE ADHESION (14 DAY AIR)					
			Dry Condition	Wet Condition	
Epoxy Grout			>4.5Kn	>3.6Kn	
BS 5980 : 1980			0.95	0.56	
			(2)		

Packaging

Kit :	Filler	Resin	Hardener
5 kg :	3.750 kg	0.900 kg	0.350 kg
1 kg :	0.750 kg	0.180 kg	0.070 kg

Packing
1kg, 5kg,

World-class Tile and Stone
Installation **Solution**



SPARKLE EPOXY GROUT

SPARKLE EPOXY GROUT

Stain Free Grout for Floor & Wall (3 Part)



DESCRIPTION Epoxy Grout is a three-part system, comprising of PART A, PART B and PART C for ease of application. The ability to fill tile / stone joints. The grout is best mixed to a smooth, creamy consistent paste. Epoxy resin-based grout has a high degree of resistance to chemicals, abrasion and higher impact resistance. The cured grout creates a tough, impermeable layer resistant to food drops, bacteria, and dirt is easily maintained in a clean condition.

FEATURES Stain less and easy to clean, easy to mix and apply.
Provides excellent chemical resistant property.
Provides hygienic, hard wearing & impervious properties.
Non-cracking or powdering.
Non-Toxic & restricts entry of bacteria / dirt.

Technical Specification

JOINT WIDTH	POT LIFE @ 27 + 2C°	CURE @ 27 + 2C°	TEMPERATURE RESISTANCE	WATER ABSORPTION	SPECIFIC GRAVITY
2-20mm	45 minutes	48hours	Prolonged - 30°C To 150° c intermittent up to 100 c°	Nil (1)	1.75
TENSILE ADHESION (14 DAY AIR)					
			Dry Condition	Wet Condition	
Epoxy Grout			>4.5Kn	>3.6Kn	
BS 5980 : 1980			0.95	0.56	
			(2)		

Packaging

Kit :	Filler	Resin	Hardener
5 kg :	3.400 kg	1.100 kg	0.500 kg
1 kg :	0.680 kg	0.220 kg	0.100 kg

Packing
1kg, 5kg,

World-class Tile and Stone
Installation **Solution**



DURATONE AD MIX

DURATONE ADMIX

Admixture for Grout



APPLICATION

Designed for use with duratone grout.
its used in place of water

KEY FEATURES & BENEFIT

- Inhibits stain causing bacteria and mold
- Inhibits powdering and cracking
- Provides a more dense and stronger cement based grout joints
- Looks in grout color-reduces problems with faded or biotech colour in grouts
- Water and frost resistant-prevents damage to grouts from weathering frost and thermal shock
- Improves compressive strength and flexibility
- Easy to clean & use

USES

Used in place of water duratone grout admix improves the performance of portland cement grout for all types of ceramic tiles, bricks, Marbles and natural stone

SELF LIFE & STORAGE

Factory sealed bottle of this products are guaranteed for two (2) years. if stored at temperature $>32^{\circ}$ (0°C) and $<110^{\circ}\text{F}$ (43°C)

Packing

200 ml,
500 ml,
5 ltr.

World-class Tile and Stone
Installation **Solution**



DURATONE TILES CLEANER

DURATONE TILES CLEANER

Tile care - Cleaners



DESCRIPTION

Duratone tile cleaner is a high quality fast acting acid based cleaner for regular cleaning of dirt and stains on tiles surfaces. its designed for daily maintenance of tiles

APPLICATION

- Interior & exterior use
- Glazed ceramic tiles
- Vitrified Tiles
- Porcelain tiles. Glass tiles. etc


ADVANTAGES

- Powerful formula
- Fast acting
- Easy to use
- Removes cement film
- General purpose tile cleaner

Do not use on marble and natural stone and cp fittings

Packing
1 ltr.

World-class Tile and Stone
Installation **Solution**



DURATONE CAM BOND

Integral Liquid Water Proofing Compound for
Concrete & Plaster (Add Mixture)



Product Details

Duratone Cem Bond is specially formulated integral liquid waterproofing compound composed of surface active Plasticising agents, polymers & additives. It is used as an additive for cement concrete, mortar & plasters. It makes concrete cohesive and prevents segregation.

Areas of Application Waterproofing of concrete and sand-cement mortars used in

- * Basements
- * Roof slabs and screeds
- * Water tanks & water retaining structures
- * External plastering
- * Bathrooms and balconies
- * Sumps and drains

Method of Application

- * Charge cement & aggregates to concrete mixer as per the mix design, mix in dry state for 1-2 minutes.
- * Start addition of 75-80% mixing water & mix for 2-3 minutes.
- * Duratone Cem Bond /Super Bond is added as per the recommended dosage into the remaining mixing / gauging water, then add to concrete mixer & mix for another 2 minutes.
- * Place the concrete or apply plaster, as needed .
- * Cure the applied mortar or concrete as per good construction practices.

Shelf Life & Storage


Shelf life is 12 months from the date of manufacturing in unopened condition. Store in a cool & dry place.

Dosage

100 to 300 ml per 50 kg bag of cement

Packing
200 ml, 1, 5,
20 & 220 liter

World-class Tile and Stone
Installation **Solution**



DURATONE SUPER LATEX

SBR Latex for Waterproofing & Repairs



Packing
250 g, 1 kg,
5 kg & 20 Kg

Product Details

Duratone **Super Latex - 555** SBR is a highly potent and versatile SBR based liquid for high performance applications in waterproofing and repairs.

Technical Information

- Type - Styrene Butadiene Polymer Liquid
- Color - White
- Specific Gravity - 1.02 ± 0.02
- Storage Condition - Free from frost
- Solid Content - 44 ± 1%
- For best result - use before 1 year if unopened Consumption - 1 kg of super latex will cover 70 - 80 sq. ft. area in 2 coats for a proportion mix 1:4:7 (Super Latex : Water : Cement)

World-class Tile and Stone
Installation **Solution**

DURATONE WALL PUTTY

Tile care - Cleaners



DESCRIPTION

Duratone wallputty is unique formulation of white cement and high performance special chemicals with polymer-strengthens the surface its also protects expensive paints from moisture and dampness

APPLICATION

Ideal for interior and exterior walls surface

**KEY FEATURES
& BENEFIT**

- Easy to mix and apply
- Suitable for new and old surface
- Strong bonding strength and water resistant
- Can be apply directly over concrete and cement plaster
- Economical & easy to use
- Protects paint from moisture and flaking
- Does not require curing
- Long lasting and improves coverage for costly paints
- Can be applied on wet/dry surface no need to primer
- Prevents growth for fungous and algar

COVERAGE

16 to 20 Sq.ft per kg for 2 . maintaining a maximum thickness of 1.5 mm on smooth plaster surface

Packing
1 ltr.

**World-class Tile and Stone
Installation Solution**

CLW+

CLW+ is an interpol waterproofing liquid admixture which has to be used with cement in concrete and plaster mix it helps in making concrete and plaster more cohesive and watertight, thus making it waterproof



DESCRIPTION

Duratone wallputty is unique formulation of white cement and high performance special chemicals with polymer-strengthens the surface its also protects expensive paints from moisture and dampness

APPLICATION

Ideal for interior and exterior walls surface

**KEY FEATURES
& BENEFIT**

- Foundation / Basement ? RCC pillars
- Concrete
- Plaster
- Water Tanks

COVERAGE

- Makes concrete more cohesive & protect steel bar corrosion
- Increases strength of concrete
- Decreases plaster rebound loss
- Reduces the permeability of water into concrete and stops rising dampness
- Reduces shrinkage crack development plaster & concrete

DOSE

200 ml for 50 kg bag of cement

PACKING

1 Ltr, 5 Ltr & 20 Ltr

**Packing
1 ltr.**